

Dati tecnici: versione per aria

Technical data: compressed air version

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Portata / Flow NL/min	Press. bar	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code	Bobina / Coil
	1/8"	Comando elettrico monostabile N.C. Electrical control monostable N.C.	5,5	600	3 ÷ 10	15	18	-MF-F2500S	M1-M3
	1/4"		8	1100	3 ÷ 10	20	22	-MF-F2510S	M1-M3
	3/8"		10	1500	3 ÷ 10	20	22	-MF-F2520S	M1-M3
	1/2"		15	5500	3 ÷ 10	18	25	-MF-F2530S	M2
	3/4"		19	6500	3 ÷ 10	18	25	-MF-F2540S	M2
	1"		25	13500	3 ÷ 10	20	30	-MF-F2545S	M2
	1 1/2"		39	35000	3 ÷ 10	45	30	-MF-F2560	M2
	2"		50	60000	3 ÷ 10	50	35	-MF-F2580	M2

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Portata / Flow NL/min	Press. bar	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code	Bobina / Coil
	1/8"	Comando elettrico monostabile N.A. Electrical control monostable N.O.	5,5	600	3 ÷ 10	15	18	-MF-F2501S	M1-M3
	1/4"		8	1100	3 ÷ 10	20	22	-MF-F2511S	M1-M3
	3/8"		10	1500	3 ÷ 10	20	22	-MF-F2521S	M1-M3
	1/2"		15	5500	3 ÷ 10	18	25	-MF-F2531S	M1-M3
	3/4"		19	6500	3 ÷ 10	18	25	-MF-F2541S	M2
	1"		25	13500	3 ÷ 10	20	30	-MF-F2546S	M2
	1 1/2"		39	35000	3 ÷ 10	45	30	-MF-F2561	M2
	2"		50	60000	3 ÷ 10	50	35	-MF-F2581	M2

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Portata / Flow NL/min	Press. bar	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code
	1/8"	Comando pneumatico monostabile N.C. Pneumatic control monostable N.C.	5,5	600	3 ÷ 10	05	08	-MF-F2600S
	1/4"		8	1100	3 ÷ 10	10	12	-MF-F2601S
	3/8"		10	1500	3 ÷ 10	10	12	-MF-F2606S
	1/2"		15	5500	3 ÷ 10	08	15	-MF-F2603S
	3/4"		19	6500	3 ÷ 10	08	15	-MF-F2610S
	1"		25	13500	3 ÷ 10	10	20	-MF-F2615S
	1 1/2"		39	35000	3 ÷ 10	45	30	-MF-F2620
	2"		50	60000	3 ÷ 10	50	35	-MF-F2680

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Portata / Flow NL/min	Press. bar	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code
	1/8"	Comando pneumatico monostabile N.A. Pneumatic control monostable N.O.	5,5	600	3 ÷ 10	05	08	-MF-F2700S
	1/4"		8	1100	3 ÷ 10	10	12	-MF-F2701S
	3/8"		10	1500	3 ÷ 10	10	12	-MF-F2706S
	1/2"		15	5500	3 ÷ 10	08	15	-MF-F2703S
	3/4"		19	6500	3 ÷ 10	08	15	-MF-F2710S
	1"		25	13500	3 ÷ 10	10	20	-MF-F2715S
	1 1/2"		39	35000	3 ÷ 10	45	30	-MF-F2720
	2"		50	60000	3 ÷ 10	40	35	-MF-F2780