



Dati tecnici: versione vuoto asservito

Technical data: servoassisted by vacuum

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Pompa / Pump MQ/h	Vuoto / Vacuum max mm HG	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code	Bobina / Coil
	1/4"	Comando elettrico monostabile N.C. <i>Electrical control monostable N.C.</i>	8	4	150/755	25	18	-MF-G3210S	M2
	3/8"		15	10	150/755	25	18	-MF-G3214S	M2
	1/2"		15	20	150/755	30	18	-MF-G3222S	M2
	3/4"		19	35	150/755	30	18	-MF-G3232S	M2
	1"		25	90	150/755	40	20	-MF-G3242S	M2
	1 1/2"		39	100	150/755	75	50	-MF-G3256	M2

SIMBOLO / SIMBOL	Taglia / Size	Funzione / Function	Ø mm	Pompa / Pump NL/min	Vuoto / Vacuum max bar	Tempo / Time ms. Ecc. 12 Dis.10		Codice / Code	Bobina / Coil
	1/4"	Comando elettrico monostabile N.A. <i>Electrical control monostable N.O.</i>	8	4	150/755	20	15	-MF-G3211S	M2
	3/8"		15	10	150/755	20	15	-MF-G3215S	M2
	1/2"		15	20	150/755	20	20	-MF-G3223S	M2
	3/4"		19	35	150/755	20	20	-MF-G3233S	M2
	1"		25	90	150/755	25	20	-MF-G3243S	M2
	1 1/2"		39	100	150/755	70	60	-MF-G3257	M2